Applicant: Yao Wang, et al. U.S.S.N.: 10/017.304

Filing Date: December 11, 2001 EMC Docket No.: EMC-01-201

Please amend the subject application, as follows:

Amendments to the Claims are reflected in the listing of claims which begins on page 3 of this

paper.

Remarks begin on page 6 of this paper.

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

Application.

Listing of Claims:

1. (Previously presented) A method, operable on a computer system, for managing

network resources for copying data stored on a first data storage system to a second data storage

system in a data replication process, wherein each data storage system includes an array of data

storage devices on which data involved in the copying is stored, the method comprising the

computer-executed steps of:

requesting from a server for services on a network, an allocation of bandwidth for data

copying from the first data storage system to the second data storage system over the network, said

bandwidth allocation based on an estimate of the data to be copied, a number of invalid tracks

between said first and second data storage systems, and a known time period in which to copy said

data:

copying data in response to the bandwidth allocation from the server based on the

request:

Applicant: Yao Wang, et al. U.S.S.N.: 10/017,304 Filing Date: December 11, 2001 EMC Docket No : EMC-01-201

monitoring network traffic performance characteristics during the data copying; and responsive to the monitored network traffic characteristics, selectively requesting an

effect on the bandwidth allocation.

2. (Original) The method of claim 1, wherein the effect requested is to increase

bandwidth allocation.

3. (Previously presented) The method of claim 1, wherein the request is in

accordance with a Java-based protocol.

4. (Previously presented) The method of claim 1, wherein the effect requested is to

increase the bandwidth allocation based on not meeting at least one performance criterion.

5. (Previously presented) The method of claim 4, wherein the at least one

performance criterion is a predetermined data transfer rate.

6. (Cancelled)

7. (Previously presented) The method of claim 1, wherein monitored network traffic

characteristics includes information regarding packet latency.

8. (Previously presented) The method of claim 1, wherein the monitored network

traffic characteristics includes information regarding packet loss.

9.-15. (Cancelled)

16. (Previously presented) The method of claim 1, wherein the data replication is

carried out in accordance with a replication policy.

17. (Original) The method of claim 16, wherein the replication policy defines replication

groups includes devices distributed between the first and second data storage systems and the

data replication process is completed when all devices in the replication groups are synchronized.

18. (Previously presented) A networked computer system for managing network

resources for copying of data from a first data storage system to a second data storage system in

Applicant: Yao Wang, et al. U.S.S.N.: 10/017,304

Filing Date: December 11, 2001 EMC Docket No.: EMC-01-201

a data replication process, wherein each data storage system includes an array of data storage

devices on which data involved in the copying is stored, the network computer system

comprising:

a server for providing services over the network; and

a network communication device capable of enabling the method steps of:

requesting from the server an allocation of bandwidth for data copying from the

first data storage system to the second data storage system over the network based on an

estimate of the data to be copied, a number of invalid tracks between said first and second

data storage systems, and a known time period in which to copy said data;

copying data in response to the bandwidth allocation from the server based on the

request;

monitoring network traffic performance characteristics during the data copying;

and

responsive to the monitored network traffic characteristics, selectively requesting

an effect on the bandwidth allocation.

19 (Cancelled)

(Previously presented) The system of claim 19, wherein the request is in

accordance with a Java-based protocol.

(Previously presented) The system of claim 18, wherein the effect requested is to

increase bandwidth allocation based on not meeting at least one performance criterion.

(Previously presented) The system of claim 21, wherein the at least one

performance criterion is based on a predetermined data transfer rate.

23. (Cancelled)

(Previously presented) The system of claim 18, wherein the monitored network

Applicant: Yao Wang, et al. U.S.S.N.: 10/017.304

Filing Date: December 11, 2001 EMC Docket No.: EMC-01-201

traffic characteristics include information regarding packet latency.

25. (Previously presented)The system of claim 18, wherein the monitored network

traffic characteristics including information regarding packet loss.

26. (Previously presented)The system of claim 18, wherein the data replication is

carried out in accordance with a replication policy.

27. (Original) The system of claim 26, wherein the replication policy defines

replication groups including devices distributed between the first and second data storage

systems and the data replication process is completed when all devices in the replication groups

are synchronized.

28. (Previously presented)A program product for managing network resources for

copying data stored in a data storage environment, the program product being from management

of data and being comprised of:

computer-executable logic provided from a computer-readable medium, when loaded

into a computer system causes the computer system to execute the steps of:

requesting from a server fro services on a network, an allocation of bandwidth for

data copying from a first data storage system to a second data storage system over the

network based on estimate of the data to be copied, a number of invalid tracks between

said first and second data storage systems, and a known time period in which to copy said data; copying data in response to the bandwidth allocation from the server based on the

request;

monitoring network traffic performance characteristics during the data copying;

and

responsive to the monitored network traffic characteristics, selectively requesting

an effect on the bandwidth allocation.